Office Action Dated: September 27, 2007

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

(Currently Amended) An authentication system for authenticating a user's signature
as electronically inputted into the system by a manual input device providing an output indicative
of its location with respect to time when manipulated by the user, the system comprising:

[[(a)]] a first_extraction means for extracting angle and distance data relating to different parts of the user's signature inputted into the system by the manual input device to obtain a signature trace;

normalization means for normalizing the signature trace based upon a time to obtain a normalized signature trace;

a second extraction means for extracting angle and distance data relating to different parts of the normalized signature trace;

- [[(b)]] registration means for setting up a reference data file empiled from comprising angle and distance data relating to extracted from a plurality of samples of the user's signature inputted into the system by the user by means of the manual input device during a registration phase;
- [[(c)]] comparison means for comparing the angle and distance data extracted by the extraction means from the user's signature inputted into the system during an authentication phase to reference angle and distance data held in the reference data file, according to defined verification criteria; and
- [[(d)]] verification means for providing an output indicative of an appropriate match between the inputted signature to be authenticated and the reference data in dependence on the result of the comparison -thereby-providing verification of the user's signature.

DOCKET NO.: **03-0005/0595USAP135730 PATENT

Application No.: 10/500,854

Office Action Dated: September 27, 2007

2. (Original) A system according to claim 1, wherein the extraction means is adapted to extract data relating to a plurality of different points of the user's signature including data relating some of said points to other points in the user's signature as inputted into the system by the manual input device.

- 3. (Original) A system according to claim 2, wherein the extraction means is adapted to extract data relating to a plurality of different points of the user's signature including data relating each of a number of said points to an immediately preceding point in the user's signature as inputted into the system by the manual input device.
- 4. (Original) A system according to claim 2 or 3, wherein the extraction means is adapted to extract data relating to a plurality of different points of the user's signature including data relating a last point to a first point in the user's signature as inputted into the system by the manual input device.
- (Previously presented) A system according to claim 1, wherein the extraction means includes angle extract means for extracting angle data concerning the relative angular positions of a plurality of points of the user's signature.
- 6. (Previously presented) A system according to claim 1, wherein the extraction means includes distance extract means for extracting distance data concerning the relative distances apart of a plurality of points of the user's signature.
- 7. (Previously presented) A system according to claim 1, wherein the extraction means includes timing extract means for extracting timing data indicative of the relative times between execution of different parts of the user's signature, and the comparison means is adapted to compare the extracted timing data with reference timing data in the reference data file.

Office Action Dated: September 27, 2007

8. (Previously presented) A system according to claim 1, wherein password verification means is provided for verifying input of a required password, as determined by reference password means, by the user using a keyboard input device.

- 9. (Original) A system according to claim 8, wherein timing verification means is provided for verifying input of the password by the user with the required timing, as determined by reference timing means, using the keyboard input device.
- 10. (Currently amended) A system according to claim 9, wherein the timing verification means includes means for verifying [[the]] <u>a plurality of</u> hold times for which the relevant keys of the keyboard input device are depressed during input of the password, and means for verifying [[the]] <u>a plurality of</u> latency times between [[the]] <u>a release</u> of one key and [[the]] <u>a depression of [[the]]</u> a following key during use of the keyboard input device to enter the password.
- 11. (Previously presented) A system according to claim 1, wherein user name input means is provided for receiving a user name inputted into the system to identify the identity of the user for the purposes of selection of the required reference data file for that user.
- 12. (Previously presented) A system according to claim 1, wherein the comparison means incorporates at least one neural network for determining the verification criteria by which a match is to be judged.

DOCKET NO.: **03-0005/0595USAP135730 PATENT

Application No.: 10/500,854

Office Action Dated: September 27, 2007

13. (Previously presented) A system according to claim 1, wherein the extraction means is adapted to extract data relating to different features of the user's signature selected according to the fitness of such features to discriminate the user's signature for the purposes of verification and determined by a fitness function relating the relative fitness of the features to their form and

number.

14. (Original) A system according to claim 13, wherein the fitness function is ontimised

by an optimisation algorithm, such as a genetic algorithm.

15. (Currently Amended) A system according to claim 1, wherein further comprising a

training means is provided for training the system to refine the verification criteria by which a match is to be judged on the basis of angle and distance data relating to a plurality of samples of

the user's signature inputted into the system by the user during the registration phase and generated false samples.

16. (Previously presented) A system according to claim 1, wherein the verification

means is adapted to provide a reject output indicative of non-matching of one or more

verification criteria only after completion of all the verification procedures.

Page 6 of 19

DOCKET NO.: **03-0005/0595USAP135730

Application No.: 10/500,854

Office Action Dated: September 27, 2007

17. (New) A method for authenticating a user's signature as electronically inputted into the system by a manual input device providing an output indicative of its location with respect to time when manipulated by the user, comprising:

extracting angle and distance data relating to different parts of the user's signature inputted into the system by the manual input device to obtain a signature trace;

normalizing the signature trace based upon a time to obtain a normalized signature trace;

extracting angle and distance data relating to different parts of the normalized signature trace;

creating a reference data file comprising angle and distance data extracted from a plurality of samples of the user's signature inputted into the system by the user using a manual input device during a registration phase;

comparing the angle and distance data extracted from the user's signature inputted into the system during an authentication phase to reference angle and distance data held in the reference data file, according to defined verification criteria; and

providing an output indicative of an appropriate match between the inputted signature to be authenticated and the reference data in dependence on the result of the comparison.

18. (New) The method of claim 17, wherein extracting angle and distance data comprises extracting data relating to a plurality of different points of the user's signature including data relating some of said points to other points in the user's signature as inputted into the system by the manual input device.

DOCKET NO.: **03-0005/0595USAP135730 PATENT

Application No.: 10/500,854 Office Action Dated: September 27, 2007

19. (New) The method of claim 18, wherein extracting angle and distance data

comprises extracting data relating to a plurality of different points of the user's signature including data relating each of a number of said points to an immediately preceding point in the

user's signature as inputted into the system by the manual input device.

20. (New) The method according to claim 18 or 19, wherein extracting angle and

distance data comprises extracting data relating to a plurality of different points of the user's

signature including data relating a last point to a first point in the user's signature as inputted into

the system by the manual input device.

21. (New) The method of claim 17, wherein extracting angle and distance data includes

extracting angle data concerning the relative angular positions of a plurality of points of the

user's signature.

22. (New) The method of claim 17, wherein extracting angle and distance data includes extracting distance data concerning the relative distances apart of a plurality of points of the

user's signature.

23. (New) The method of claim 17, wherein extracting angle and distance data includes

extracting timing data indicative of the relative times between execution of different parts of the

user's signature, and the comparison means is adapted to compare the extracted timing data with

reference timing data in the reference data file.

24. (New) The method of claim 17, further comprising verifying an input of a required

password, as determined by reference password, by the user using a keyboard input device.

25. (New) The method of claim 24, further comprising verifying the input of the

password by the user with a required timing, as determined by a reference timing, using the

keyboard input device.

Page 8 of 19

DOCKET NO.: **03-0005/0595USAP135730 PATENT

Application No.: 10/500,854

Office Action Dated: September 27, 2007

26. (New) The method of claim 25, wherein verifying the input further comprises:

verifying a plurality of hold times for which the relevant keys of the keyboard input

device are depressed during input of the password; and

verifying a plurality of latency times between the release of one key and the depression of

the following key during use of the keyboard input device to enter the password.

27. (New) The method of claim 17, further comprising receiving a user name inputted

into the system to identify the identity of the user for the purposes of selection of the required

reference data file for that user.

28. (New) The method of claim 17, wherein comparing the angle and distance data

incorporates at least one neural network for determining the verification criteria by which a

match is to be judged.

29. (New) The method of claim 17, wherein extracting angle and distance data extracts

data relating to different features of the user's signature selected according to the fitness of such

features to discriminate the user's signature for the purposes of verification and determined by a

fitness function relating the relative fitness of the features to their form and number.

30. (New) The method of claim 29, wherein the fitness function is optimised by an

optimisation algorithm, such as a genetic algorithm.

31. (New) The method of claim 17, further comprising training to refine the verification

criteria by which a match is to be judged on the basis of angle and distance data relating to a plurality of samples of the user's signature inputted by the user during the registration phase and

generated false samples.

Page 9 of 19

PATENT

DOCKET NO.: **03-0005/0595USAP135730

Application No.: 10/500,854

Office Action Dated: September 27, 2007

32. (New) The method of claim 17, wherein providing verification of the user's signature provides a reject output indicative of non-matching of one or more verification criteria

only after completion of all the verification procedures.

33. (New) A method for authenticating a user's signature as electronically inputted into

the system by a manual input device providing an output indicative of its location with respect to

time when manipulated by the user, comprising:

extracting angle and distance data relating to different parts of a user's signature inputted

device to obtain a signature trace;

normalizing the signature trace based upon a time to obtain a normalized signature trace;

and

extracting angle and distance data relating to different parts of the normalized signature

trace.

34. (New) The method of claim 33, further comprising:

setting up a reference data file comprising angle and distance data relating to a plurality

of samples of the user's signature inputted during a registration phase, wherein the plurality of

samples of the user's signature are normalized based upon a time to obtain a plurality of normalized samples.

nzeu sampies.

35. (New) The method of claim 34, further comprising:

comparing the angle and distance data extracted from the user's signature inputted during

an authentication phase to reference angle and distance data held in the reference data file,

according to defined verification criteria.

Page 10 of 19

Office Action Dated: September 27, 2007

36. (New) The method of claim 35, further comprising:

providing an output indicative of an appropriate match between the inputted signature to be authenticated and the reference data in dependence on the result of the comparison, thereby

providing verification of the user's signature.

37. (New) The method of claim 34, further comprising:

training to refine the verification criteria by which a match is to be judged on the basis of

angle and distance data relating to a plurality of samples of the user's signature during the

registration phase and generated false samples.

38. (New) A computer-readable storage medium having computer-readable instructions

stored thereon for authenticating a user's signature, the computer-readable instructions

comprising instructions for:

extracting angle and distance data relating to different parts of a user's signature inputted

to obtain a signature trace;

normalizing the signature trace based upon a time to obtain a normalized signature trace;

and

extracting angle and distance data relating to different parts of the normalized signature

trace.

Page 11 of 19

upon a time to obtain a plurality of normalized samples.

Office Action Dated: September 27, 2007

for:

39. (New) The computer-readable medium of claim 38, further comprising instructions

setting up a reference data file comprising angle and distance data extracted from a plurality of samples of the user's signature inputted using a manual input device during a registration phase, wherein the plurality of samples of the user's signature are normalized based

40. (New) The computer-readable medium of claim 39, further comprising instructions for:

comparing the angle and distance data extracted from the user's signature inputted into the system during an authentication phase to reference angle and distance data held in the reference data file, according to defined verification criteria.

41. (New) The computer-readable medium of claim 40, further comprising instructions for:

providing an output indicative of an appropriate match between the inputted signature to be authenticated and the reference data in dependence on the result of the comparison, thereby providing verification of the user's signature.

42. (New) The computer-readable medium of claim 39, further comprising instructions for:

training to refine the verification criteria by which a match is to be judged on the basis of angle and distance data relating to a plurality of samples of the user's signature during the registration phase and generated false samples.

DOCKET NO.: **03-0005/0595USAP135730

Application No.: 10/500,854

Office Action Dated: September 27, 2007

43. (New) A system for authenticating a user's signature, the system comprising:

an input apparatus, wherein the input apparatus is configured to provide an output indicative of the location of the input apparatus with respect to time when the input apparatus is manipulated:

a computing apparatus, wherein the computing apparatus is configured to:

extract angle and distance data relating to different parts of a user's signature outputted by the input apparatus to obtain a signature trace;

normalize the signature trace based upon a time to obtain a normalized signature trace; and

extract angle and distance data relating to different parts of the normalized signature trace.

44. (New) The system of claim 43, further comprising:

a reference data file comprising angle and distance data relating to a plurality of samples of the user's signature inputted using a manual input device during a registration phase, wherein the plurality of samples of the user's signature are normalized based upon a time to obtain a plurality of normalized samples.

45. (New) The system of claim 44, further comprising:

a comparator apparatus configured to compare the angle and distance data extracted from the user's signature inputted into the system during an authentication phase to reference angle and distance data held in the reference data file, according to defined verification criteria.

PATENT

DOCKET NO.: **03-0005/0595USAP135730 **Application No.:** 10/500,854

Office Action Dated: September 27, 2007

46. (New) The system of claim 45, further comprising:

an output apparatus configured to provide an output indicative of an appropriate match between the inputted signature to be authenticated and the reference data in dependence on the result of the comparison, thereby providing verification of the user's signature.

47. (New) The system of claim 44, further comprising:

a trainer configured to refine the verification criteria by which a match is to be judged on the basis of angle and distance data relating to a plurality of samples of the user's signature during the registration phase and generated false samples.

48. (New) A method of verifying a user's signature, comprising:

comparing angle and distance data from an input signature during an authentication phase to reference angle and distance data, according to defined verification criteria, wherein the angle and distance data comprises extracted angle and distance data relating to different parts of a normalized signature trace, and wherein the reference angle and distance data is obtained from a reference data file comprising angle and distance data relating to a plurality of samples of the user's signature, wherein the plurality of samples of the user's signature are normalized based upon a time to obtain a plurality of normalized samples; and

providing an output indicative of an appropriate match between the inputted angle and distance data and the reference angle and distance in dependence on the result of the comparison, thereby providing verification of the user's signature.

49. (New) The method of claim 48, wherein extracting angle and distance data extracts data relating to different features of the user's signature selected according to the fitness of such features to discriminate the user's signature for the purposes of verification and determined by a fitness function relating the relative fitness of the features to their form and number.

Office Action Dated: September 27, 2007

50. (New) The method of claim 49, wherein the fitness function is optimised by an optimisation algorithm, such as a genetic algorithm.

51. (New) The method of claim 48, further comprising:

training to refine the verification criteria by which a match is to be judged on the basis of angle and distance data relating to a plurality of samples of the user's signature during the registration phase and generated false samples.

- 52. (New) The method of claim 48, further comprising verifying an input of a required password, as determined by reference password, by the user using a keyboard input device.
- 53. (New) The method of claim 52, further comprising verifying the input of the password by the user with a required timing, as determined by a reference timing, using the keyboard input device.
 - 54. (New) The method of claim 53, wherein verifying the input further comprises:

verifying a plurality of hold times for which relevant keys of the keyboard input device are depressed during input of the password; and

verifying a plurality of latency times between the release of one key and the depression of the following key during use of the keyboard input device to enter the password.